

## PERFORMANCE DATA

Type 6651 Daylite Par® using 6,000 watt, 5600°K HMI Lamp.

Distance	No Lens (3.2°)		Narrow (11.6°)		Medium (32° x 15.5°)		Wide (52.4° x 19.8°)		Extra-Wide (69.6°)	
	Diameter/Ft.	F.C.	Diameter/Ft.	F.C.	W x H/Ft.	F.C.	W x H/Ft.	F.C.	Diameter/Ft.	F.C.
20	1.1	26,219	4.1	14,438	11.5 x 5.4	3,315	19.7 x 7.0	1,790	27.8	570
25	1.4	16,780	5.1	9,240	14.3 x 6.8	2,122	24.6 x 8.7	1,146	34.8	365
30	1.7	11,653	6.1	6,417	17.2x 8.2	1,473	29.5 x 10.5	796	41.7	253
40	2.2	6,555	8.1	3,609	22.9 x 10.9	829	39.4 x 14.0	448	55.6	143
50	2.8	4,195	10.2	2,310	28.7 x 13.6	530	49.2 x 17.5	286	69.5	91
60	3.4	2,913	12.2	1,604	34.4 x 16.3	368	59.0 x 20.9	199	83.4	63
75	4.2	1,864	15.2	1,027	43.0 x 20.4	236	73.8 x 26.2	127	104.3	41
100	5.6	1,049	20.3	578	57.3 x 27.2	133	98.4 x 34.9	72	139.0	23
125	7.0	671	25.4	370	71.7 x 34.0	85	123.0 x 43.6	46	173.8	15
150	8.4	466	30.5	257	86.0 x 40.8	59	147.6 x 52.4	32	208.5	10
175	9.8	342	35.6	189	100.4 x 47.6	43	172.2 x 61.1	23	243.3	7
200	11.2	262	40.6	144	114.7 x 54.4	33	196.8 x 69.8	18	278.0	6

\*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.