

SPECIFICATIONS

HEAD: Type 6651 6,000 Watts

RATING: 135 volts, A.C., 65 amps max.

SOCKET: G38, Heavy duty electrical grade porcelain body with friction type bi-post brass inserts.

SWITCH: ON and OFF push-button switches mounted on rear of fixture. May be re-ignited when hot.

SAFETY SWITCH: Interlock micro-switch at door shuts off power to globe sockets when door is opened. Globe cannot be turned on until door is closed.

CABLE: Attached 7-conductor, with male interlocking "Veam" type connector.

HEAD CONSTRUCTION: Rugged construction of cast and sheet aluminum.

YOKE: Aluminum tubing and cast aluminum trunnions with 1 $\frac{1}{8}$ " dia. Junior Pin.

REFLECTOR: Highly polished aluminum Brytal finished parabolic reflector.

BEAM CONTROL: Four accessory lenses (listed below), used individually, change the beam pattern from Narrow to Extra Wide Flood. The beam pattern created by the lenses may be rotated within the diffuser clips for vertical or horizontal beam orientation. Further spot to flood adjustments can be made using the focus knob on the rear of the fixture.

FINISH: Clear Anodized Aluminum/Black Powder Coated Enamel.

SIZE: 29" x 19 $\frac{1}{2}$ " x 21"

HEAD WEIGHT: 63 lbs. (w/cable)