

PERFORMANCE DATA

Type 6731 2,000 Watt Tungsten Par[®] using 2,000 watt, 3200°K Tungsten Lamp.

Distance	No Lens (9°)		Narrow (12.6°)		Medium (23.7° x 14.2°)		Wide (52.4° x 22.6°)		Extra-Wide (50.2°)	
	Diameter/Ft.	F.C.	Diameter/Ft.	F.C.	W x H/Ft.	F.C.	W x H/Ft.	F.C.	Diameter/Ft.	F.C.
10	1.6	5,619	2.2	2,874	4.2 x 4.2	1,658	4.0 x 9.8	602	9.4	294
20	3.1	1,405	4.4	718	5.0 x 8.4	414	8.0 x 19.7	150	18.7	74
30	4.7	624	6.6	319	7.5 x 12.6	184	12.0 x 29.5	67	28.1	33
40	6.3	351	8.8	180	10.0 x 16.8	104	16.0 x 39.4	38	37.5	18
50	7.9	225	11.0	115	12.5 x 21.0	66	20.0 x 49.2	24	46.8	12
60	9.4	156	13.2	80	14.9 x 25.2	46	24.0 x 59.0	17	56.2	8
75	11.8	100	16.6	51	18.7 x 31.5	29	30.0 x 73.8	11	70.3	5
100	15.7	56	22.1	29	24.9 x 42.0	17	40.0 x 98.4	6	93.7	3
125	19.7	18	27.6	18	31.1 x 52.5	11	50.0 x 123.0	4	117.1	2

*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.