

SPECIFICATIONS

HEAD: Type 6731 2,000 Watt Tungsten Par®

RATING: 120/240 volts, A.C. or D.C., 20 amps max.—2,000 watts max.

SOCKET: G38, Heavy duty electrical grade porcelain body with friction type bi-posts brass inserts.

SWITCH: 20 amp, 240 volt heavy duty, double pole. Mounted in trough.

CABLE: Attached — 25 ft. Type SO, 3 conductor #12 AWG.

(when ordering specify type of plug required).

HEAD CONSTRUCTION: Rugged construction of cast and sheet aluminum.

YOKE: Aluminum tubing and cast aluminum trunnions with $5/8$ " dia. Baby Receiver.

REFLECTOR: Highly polished aluminum Brytal finished parabolic reflector.

FINISH: Clear Anodized Aluminum/Maroon Powder Coated Enamel.

SIZE: 11 $1/4$ " x 11 $1/2$ " x 23" (with yoke).

11 $1/4$ " x 11 $1/2$ " x 18" (without yoke).

HEAD WEIGHT: 20 lbs. (w/yoke & cable).

BEAM CONTROL: Five accessory lenses (listed below), used individually, change the beam pattern from Narrow to Extra Wide Flood. The beam pattern created by the lenses may be rotated within the diffuser clips for vertical or horizontal beam orientation. Further spot to flood adjustments can be made using the focus knob on the rear of the fixture.