



Specifications

- Head:** Type MP100FDTF Daylite (5600K)
- Includes:** 4-Way Barn Door, Power Supply, Power Cable (14ft/4m), DMX Cable (10ft/3m), Tungsten (3200K) Filter
- Rating:** 24V DC, 100-240V AC, 100W
- Light Source:** (1) 100 Watt high output Mole-Richardson LED. 5600K 95CRI Daylite
- Dimming:** Flicker Free, Direct DC Dimming
Local Dimmer 100% - 0% (Minimal Color Shift)
DMX Dimmer 100% - 0% (Minimal Color Shift)
- Control:** DMX512-A In and Out. Manual DMX Address Selector
- Condenser:** 5 in (125mm) Borosilicate Glass Fresnel
- Beam Angle:** 10° to 65°
- Focusing:** Rotating Knob on Back
- Cooling:** Passive-Forced Air
- Construction:** Aluminum and Plastic
- Yoke:** Aluminum w/Standard 5/8 in (16mm) Receiver
- Compliance:** RoHS. CE
- IP Rating:** 30
- Finish:** Black
- Size:** 10 in/254mm(d) x 9 in/229mm(w) x 16 in/406mm(h)
- Head Weight:** 6lbs/2.72kg
- LED Display:** 0-100% Intensity
1-512 DMX Channels

Accessories

V-Mount Battery Adapter

Item Number

MP100EBAV

Performance Data

Using (1) 100 Watt high output Mole-Richardson LED.

Distance Feet (Meters)	Light Intensity Maximum Flood Foot Candles (Lux) Daylite (5600K)	Light Intensity Maximum Flood Foot Candles (Lux) Tungsten (3200K Filter)	Light Intensity Maximum Spot Foot Candles (Lux) Daylite (5600K)	Light Intensity Maximum Spot Foot Candles (Lux) Tungsten (3200K Filter)
10 (3)	60 (642)	45 (482)	465 (4,976)	350 (3,745)
5 (1.5)	180 (1,926)	120 (1,284)	1400 (14,980)	900 (9,630)



MP100EBAV
V-Mount Battery Adapter

