


Performance Data

Using (1) 1500 Watt high output single LED.



3200K TUNGSTEN		
Foot Candles (Lux)	FLOOD	1400 (16000)
	SPOT	2800 (32000)
5600K DAYLITE		
Foot Candles (Lux)	FLOOD	1700 (19000)
	SPOT	3400 (38000)
Beam Diameter Feet (meters)	FLOOD	12 (3.7)
	SPOT	5 (1.5)

Features

High output, single source proprietary Mole-Richardson LED powered by house circuit, green & magenta correction, factory preset & variable-color temps, 4-channel DMX, LumenRadio, RDM, dual user interface for local control – 2.8" LCD touch-screen and twist & push selector, Bluetooth connectivity via Mole-Richardson iOS App, firmware upgradeable and user presets

Specifications

Head: Type 9541 Variable-Color. 14" Vari-Tener LED

Rating: 90-250 Volts AC, 50-60Hz, 1500 Watts, 15 Amps Max
DMX Standby Draw <0.2 Amps Max 60V DC

Light Source: (1) - 1500 Watt Mole-Richardson LED
2700-6500K 95+CRI, with +/- Green

Cable: Detachable 20 ft. (6m) Cable, PowerCON TRUE1 to Edison with Inline Aluminum Toggle Switch (included in price of fixture)

Fuse: 15 Amp Slowblow Fuse Holder in Trough

Condenser: 14 in. (355mm) High Temp. Micro-Fresnel Lens Technology

Beam Angle: 20° to 55° Variable Spot to Flood (Includes Field)

Focusing: Rear Mounted Focusing Crank

Cooling: Forced Air, Fan Speed Controlled by Temperature

Construction: Aluminum

Yoke: Aluminum with Standard Junior 1 1/8 in. (29mm) Pin

DC In: 60V DC, Regulated Constant Voltage

Compliance: RoHS

IP Rating: 30

Finish: Textured Powder Epoxy Coat. Black / Red

Size: 17.70 in.(w) x 19.03 in.(d) x 25.56 in.(h)

Weight: 70 lbs/35 kg.

Accessories

Accessories	Item Number
4-Way Tenser LED Barn Door	89685
MoleDisc Diffuser Frame (18 1/2" dia.)	418103
Half Single Scrim—Stainless Steel (18 1/2" dia.)	418108S
Half Double Scrim—Stainless Steel (18 1/2" dia.)	418108D
Single Scrim—Stainless Steel (18 1/2" dia.)	418109S
Double Scrim—Stainless Steel (18 1/2" dia.)	418109D
Scrim Bag	G139

