

Features

High output, single source proprietary Mole-Richardson LED powered by house circuit, green & magenta correction, factory preset & variable-color temps, 4-channel DMX, LumenRadio, RDM, dual user interface for local control – 2.8" LCD touch-screen and twist & push selector, Bluetooth connectivity via Mole-Richardson iOS App, firmware upgradeable and user presets

Specifications

Head: Type 9501 Variable-Color. 6" Vari-Baby LED.

Rating: 90-250 Volts AC, 50-60Hz, 140 Watts, 2 Amps Max.
DMX Standby Draw <0.2 Amps Max. 30V DC

Light Source: (1) - 140 Watt Mole-Richardson LED
2700-6500K 95+ CRI, with +/- Green

Cable: Detachable 20 ft. (6m) Cable, PowerCON TRUE1 to Edison with Inline Toggle Switch (included in price of fixture)

Fuse: 2 Amp SlowBlow. Fuse holder in trough

DMX Control (Hardwire or LumenRadio): 4 Channels, Color Temp, Intensity, Plus Green, Plus Magenta

Bluetooth: Intensity and Color Control Via Mole-Richardson iOS App

Condenser: 6 in (152mm) Borosilicate Glass Fresnel

Beam Angle: 20° to 55° Variable Spot to Flood (Includes Field)

Focusing: Rear Mounted Focusing Knob

Cooling: Forced Air, Fan Speed Controlled by Temperature

Construction: Aluminum

Yoke: Aluminum with Standard 5/8 in. Receiver.

DC In: 30V DC, Regulated Constant Voltage

Compliance: RoHS.

IP Rating: 30

Finish: Textured Powder Epoxy Coat. Black / Red

Size: 10.93 in(w) x 12.39 in(d) x 14.5 in(h)


Weight: 13 lbs/5.90 kg

Accessories

Accessories	Item Number
4-Way BabyLED Barn Door	89285
Diffuser Frame (6 5/8" dia.)	40748A
Half Single Scrim—Stainless Steel (6 5/8" dia.)	407281S
Half Double Scrim—Stainless Steel (6 5/8" dia.)	407281D
Full Single Scrim—Stainless Steel (6 5/8" dia.)	407280S
Full Double Scrim—Stainless Steel (6 5/8" dia.)	407280D
Scrim Bag	G136
Snoot (Set of 3)	40747A
Molesnoot (Five-in-one) Apertures: 2", 2 1/8", 2 3/4", 3 1/8" and 3 1/2"	407184

Performance Data

Using (1) 140 Watt high output single LED.



3200K TUNGSTEN				
Foot Candles (Lux)	FLOOD	570 (6135)	105 (1130)	60 (646)
	SPOT	1100 (11840)	250 (2690)	122 (1313)
6500K DAYLITE				
Foot Candles (Lux)	FLOOD	690 (7427)	135 (1453)	670 (7212)
	SPOT	1450 (15608)	290 (3121)	150 (1615)
Beam Diameter Feet (meters)	FLOOD	3.5 (1.1)	7 (2.1)	10.5 (3.2)
	SPOT	0.9 (0.3)	1.7 (0.5)	2.6 (0.8)

