

TUDIO JR_LED

 (\mathbb{R})

`` 19.03in [483.3mm]

Ø

[#] 17.70in---[449.5mm]

3200K TUNGSTEN

320 (3444)

700 (7534)

400 (4305)

800 (8611)

9.0 (2.7)

3.0 (0.9)

1600 (17222)

3400 (36597)

4400 (47361)

6500K DAYLITE 2000 (21527)

10" Vari-Studio Junior LED

Type 9521 Variable-Color

Features

High output, single source proprietary Mole-Richardson LED powered by house circuit, green & magenta correction, factory preset & variable-color temps, 4-channel DMX, LumenRadio, RDM, dual user interface for local control – 2.8" LCD touch-screen and twist & push selector, Bluetooth connectivity via Mole-Richardson IOS App, firmware upgradeable and user presets

Specifications

Head: Type 9521 Variable-Color. 10" Vari-Studio Junior LED.
Rating: 90-250 Volts AC, 50-60Hz, 250 Watts, 3 Amps Max. DMX Standby Draw <0.2 Amps Max. 30V DC
Light Source: (1) - 250 Watt Mole-Richardson LED 2700-6500K 95+CRI , with +/- Green
Cable: Detachable 20 ff. (6m) Cable, PowerCON TRUE1 to Edison with Inline Toggle Switch (included in price of fixture)

Fuse: 5 Amp Slow-Blow. Fuse holder in trough

DMX Control (Hardwire or LumenRadio): 4 Channels, Color Temp, Intensity, Plus Green, Plus Magenta

Bluetooth: Intensity and Color Control Via Mole-Richardson iOS App

Condenser: 10 in (254mm) Borosilicate Glass Fresnel

Beam Angle: 20° to 55° Variable Spot to Flood (Includes Field)

Focusing: Rear Mounted Focusing Knob Cooling: Forced Air, Fan Speed Controlled by Temperature

Construction: Aluminum

Yoke: Aluminum with Standard Junior 1 1/8 in. (29mm) Pin

DC In: 30V DC, Regulated Constant Voltage

Compliance: RoHS.

IP Rating: 30

Finish: Textured Powder Epoxy Coat. Black / Red Size: 17.70 in(w) x 19.03 in(d) x 25.56 in(h) Weight: 24 lbs/10.90 kg

Accessories

4-Way Studio JuniorLED Barn Door	89685
Moledisc Diffuser Frame (12" dia.)	200053A
Half Single Scrim—Stainless Steel (12" dia.)	412240S
Half Double Scrim—Stainless Steel (12" dia.)	412240D
Single Scrim—Stainless Steel (12" dia.)	4122415
Double Scrim—Stainless Steel (12" dia.)	412241D
Scrim Bag	G138



Beam Diameter Feet (meters)



FLOOD

SPOT

FLOOD

SPOT

FLOOD

SPOT

17.73in 4

25.56in

[649.3mm]

Performance Data

Foot Candles (Lux)

Foot Candles (Lux)

Using (1) 250 Watt high output single LED.

12154 Montague Street, Pacoima, California 91331 U.S.A. Tel. +1-323-851-0111 • Fax. +1-323-851-5593 • Info@mole.com •mole.com © 2016 Mole-Richardson Co.

150 (1615)

350 (3767)

180 (1938)

420 (4520)

Item Number